Allowed:

Pending Claims

11/3/03

SEP-16-03 01:54PM FROM- MATTINGLY, STANGER & MALUR, P.C.

+ 703 684 1157

T-125 P 029/037 F-360

Preliminary Amendment

NIT-133-07

IN THE CLAIMS

1-29. Canceled.

- 30. (Currently Amended) a cell component recovering apparatus comprising:
- a substrate being disposed in a separation cell, wherein them sample solution containing cells is supplied on a surface of the substrate, and wherein the substrate has a plurality of independent areas are formed on theirs surface of the substrate;
- a first electrode disposed at each of the plurality of independent areas;
- a second electrode opposed to the substrate, wherein each of the cells is captured one by one separately on each of the plurality of independent areas, by applying an alternating field between the first electrodes and the second electrode; and

temperature control means for heating the surface of the substrate at one area of the <u>plurality of independent</u> areas to a predetermined temperature to destroy the cell captured at thesaid one area of the areas, to liberate cell components from the cell captured at thesaid one area of the areas into the separation cell;

wherein by introducing a washing solution, the apparatus enables liberated cell components from the cell captured in

NIT-133-07

said one area to be recovered while cells in areas other than said one area remain on the substrate, and

wherein said temperature control means individually heats different areas of said plurality of areas so as to enable recovery of cell components from said plurality of areas

wherein, by introducing a washing colution into the separation coll, whereby the colls at the areas, except for the one area of the areas, remain on the areas, respectively, the washing solution is recovered to recover the cell components liberated from the cell, and

wherein, by changing a position of the one area of the areas, the washing solution is recovered to recover the cell components liberated from the cell for each of the areas.

- 31. (Currently Amended) A cell component recovering apparatus according to claim 30, wherein the captured cell is a white blood cell.
- (Currently Amended) A cell component recovering 32. apparatus comprising:

a substrate being disposed in a separation cell, wherein thea sample solution containing cells is supplied on a surface of the substrate, and wherein the substrate has a plurality of independent areas are formed on theits surface of the substrate,

NIT-133-07

- a first electrode disposed at each of the plurality of areas:
- a second electrode opposed to the substrate, wherein each of the cells is captured one by one separately on each of the plurality areas, by applying an alternating field between the first electrodes and the second electrode;

means for identifying the positions of theone areas where thea cells-each labeled with a fluorescence-labeled substance exeis present, wherein the fluorescence-labeled substance binds to the cells to selectively label cells by a binding reaction, the fluorescence-labeled substance emits fluorescence upon irradiation with an excitation light, and the positions of thesaid one areas are is identified by detecting the fluorescence; and

temperature control means for heating the surface of the substrate at said one area of the identified positions to a predetermined temperature to destroy the cell captured at thesaid one area of the one of the identified positions, to liberate cell components from the cell captured at thesaid one area of the one of the identified positions into the separation cell;

wherein by introducing a washing solution, the apparatus enables liberated cell components from the cell captured in said one area to be recovered while cells in areas other than said one area remain on the substrate, and

NIT-133-07

wherein said temperature control means individually heats different areas of said plurality of areas so as to enable recovery of cell components from all of said plurality of areas

- wherein, by introducing a washing solution into the separation cell, whereby the cells at the areas, except for the area at the one of the identified positions, remain on the areas, respectively, the washing solution is recovered to recover the coll components liberated from the cell; and
- wherein, by changing a position of the identified positions, the washing solution is recovered to recover the cell components liberated from the cell for each of the identified positions.
- 33. (Currently Amended) A cell component recovering apparatus according to claim 32, wherein the captured cell is a white blood call.
- 34. (Currently Amended) A cell component recovering apparatus comprising:
- a substrate being disposed in a separation cell, wherein thea sample solution containing cells is supplied on a surface of the substrate, and wherein the substrate has a plurality of independent areas are formed on theits surface of the substrate;

NIT-133-07

a first electrode disposed at each of the plurality of areas;

a second electrode opposed to the substrate, wherein each of the cells is captured one by one separately on each of the plurality of areas, by applying an alternating field between the first electrodes and the second electrode;

means for identifying the positions of the one areas where thea cells labeled with the fluorescence-labeled antigen substance axeis present, wherein the fluorescence-labeled antigen substance is introduced into the separation cell to label the cells which make an antibody response to the antigen substance, the fluorescence-labeled antiqen substance emit fluorescence upon irradiation with an excitation light, and the positions of the said one areas are is identified by detecting the fluorescence; and

temperature control means for heating the surface of the substrate at said one area-of the identified positions to a predetermined temperature to destroy the cell captured at thesaid one area of the one of the identified positions, to liberate cell components from the cell captured at thesaid one area of the one of the identified positions into the separation cell;

wherein by introducing a washing solution, the apparatus enables liberated cell components from the cell captured in

NIT-133-07

said one area to be recovered while cells in areas other than said one area remain on the substrate, and

wherein said temperature control means individually heats different areas of said plurality of areas so as to enable recovery of cell components from all of said plurality of areas

-wherein, by introducing a washing solution into the separation cell, whereby the salls at the areas, except for the area as the one of the identified positions, remain on the areas, respectively, the washing solution is recovered to recover the cell components liberated from the cell; and wherein, by changing a position of the identified positions, the washing solution is recovered to recover the cell components liberated from the cell for each of the identified positions.

35. (Currently Amended) A cell component recovering apparatus according to claim 34, wherein the captured cell is a white blood cell.